

Filler metals
for welding



**Swiss
Steel**
Group





Stainless steel and alloy drawn wires for welding

Our strengths

With its two production sites, Bourg-en-Bresse (France) and San Vendemiano (Italy), Ugitech has the resources and technical expertise of a large group that is a leading supplier of stainless steels and alloys for the welding market.

Ugitech's organisation guarantees total process control, from steelmaking to final wire drawing and packaging.

R&D-Innovation

Let's work together to create solutions to meet your needs!

An integrated research centre strives to develop new products such as EXHAUST®F1, EXHAUST®F1 Evo, EXHAUST® Bi Stab and other austenitic, martensitic and duplex stainless steel grades and a wide variety of nickel- and cobalt-based grades, type 625, 686, 617, 825, etc.

They are the result of close collaboration with our customers.

Quality

- Ugitech is ISO 9001/2008, ISO 14001 certified (Bourg-en-Bresse).
- Our products meet VdTÜV Merkblatt Schweißtechnik 1153:2012 and KTA 1408.2 standards.
- Some of our products are CE marked in accordance with the requirements of EN 13479.
- Some grades are also DB (Deutsche Bahn) certified.

Our products

Grades: austenitic, ferritic, martensitic or duplex stainless steels ; nickel-copper or cobalt-based alloys.

Ugitech has a wide range of products to meet everyone's welding needs.

Dimensions

MIG welding wire

- 5 kg to 27 kg plastic spools diameter from 0.8 mm to 1.6 mm
- 5 kg to 18 kg basket spools diameter from 0.8 mm to 1.6 mm
- 250 kg drums diameter from 0.8 mm to 1.6 mm
- 250 kg to 400 kg reels diameter from 0.8 mm to 1.6 mm

SAW sub arc welding wire

- 25 kg basket rims diameter from 1.6 mm to 4.0 mm
- 250 kg to 400 kg reels diameter from 1.6 mm to 4.0 mm

TIG welding wire

- Cut to lengths of 500 or 1000 mm, stamped diameter from 1.0 mm to 4.0 mm

Electrode core wire

- Cut to length diameter from 1.6 mm to 4.0 mm
- 250 kg to 400 kg reels diameter from 2.0 mm to 4.0 mm


Our packagings

Bourg-en-Bresse **San Vendemiano (Ugitech TFA)**




MIG welding wire spools
Basket or plastic spools in individual cardboard boxes

	■	■
--	---	---




Drums for automated MIG welding
On wooden pallets

	■	■
--	---	---




TIG welding wire
Packaged in 1-5 or 10 kg boxes

		■
--	--	---



SAW welding wire
25 kg rims in individual cardboard boxes

	■	■
--	---	---



Electrode core wire
Packaged in 500 kg or 1000 kg wooden cases

		■
--	--	---

All of our packagings can be customized, neutral or Ugitech designed.



Our Stainless steel and alloy grades for welding

Grades	Chemical composition								Standards	
	C	Si	Mn	Ni	Cr	Mo	Cu	Other elements	AWS A5.9	ISO 14343-A
Austenitic										
UGIWELD™ 308LT	≤ 0.03	≤ 0.65	1.0 - 2.5	9.0 - 11.0	19.5 - 21.0	≤ 0.5	≤ 0.5		ER308L	19 9 L
UGIWELD™ 308LM	≤ 0.03	0.65 - 1.0	1.0 - 2.5	9.0 - 11.0	19.5 - 21.0	≤ 0.5	≤ 0.5		ER308LSi	19 9 L Si
UGIWELD™ 4370M	≤ 0.20	≤ 1.2	5.0 - 8.0	7.0 - 10.0	17.0 - 20.0	≤ 0.5	≤ 0.5		*(307Si)	18 8 Mn
UGIWELD™ 309L	≤ 0.03	≤ 0.65	1.0 - 2.5	12.0 - 14.0	23.0 - 25.0	≤ 0.5	≤ 0.5		ER309L	23 12 L
UGIWELD™ 309LM	≤ 0.03	0.65 - 1.0	1.0 - 2.5	12.0 - 14.0	23.0 - 25.0	≤ 0.5	≤ 0.5		ER309LSi	23 12 L Si
UGIWELD™ 4829	0.08 - 0.12	0.65 - 1.2	1.0 - 2.5	12.0 - 14.0	22.0 - 24.0	≤ 0.5	≤ 0.5		(ER309Si)	22 12 H
UGIWELD™ 310	0.08 - 0.15	≤ 0.65	1.0 - 2.5	20.0 - 22.0	25.0 - 27.0	≤ 0.5	≤ 0.5		ER310	25 20
UGIWELD™ 316LT	≤ 0.03	≤ 0.65	1.0 - 2.5	11.0 - 14.0	18.0 - 20.0	2.5 - 3.0	≤ 0.5		ER316L	19 12 3 L
UGIWELD™ 316LM	≤ 0.03	0.65 - 1.0	1.0 - 2.5	11.0 - 14.0	18.0 - 20.0	2.5 - 3.0	≤ 0.5		ER316LSi	19 12 3 L Si
UGIWELD™ 318M	≤ 0.08	0.65 - 1.0	1.0 - 2.5	11.0 - 14.0	18.0 - 20.0	2.5 - 3.0	≤ 0.5	Nb: 10xC - 1.0	(ER318)	19 12 3 Nb Si
UGIWELD™ 347	≤ 0.08	≤ 0.65	1.0 - 2.5	9.0 - 11.0	19.0 - 21.0	≤ 0.5	≤ 0.5	Nb: 10xC - 1.0	ER347	19 9 Nb
UGIWELD™ 347M	≤ 0.08	0.65 - 1.0	1.0 - 2.5	9.0 - 11.0	19.0 - 21.0	≤ 0.5	≤ 0.5	Nb: 10xC - 1.0	ER347Si	19 9 Nb Si
UGIWELD™ 4455	≤ 0.03	0.30 - 0.65	5.0 - 9.0	15.0 - 18.0	19.0 - 22.0	2.5 - 3.0	≤ 0.5	N: 0.1 - 0.2	ER316LMn	20 16 3 Mn N L
UGIWELD™ 385	≤ 0.025	≤ 0.5	1.0 - 2.5	24.0 - 26.0	19.5 - 21.5	4.2 - 5.2	1.2 - 2.0		ER385	20 25 5 Cu L
UGIWELD™ B6N	≤ 0.025	≤ 1.0	1.0 - 2.5	24.0 - 26.0	19.5 - 21.5	4.2 - 5.2	1.2 - 2.0	N: 0.1 - 0.2	(ER385)	20 25 5 Cu N L
Ferritic Martensitic										
UGIWELD™ 409Nb	≤ 0.08	≤ 1.0	≤ 0.8	≤ 0.6	10.5 - 13.5	≤ 0.5	≤ 0.75	Nb: 10xC - 0.75	ER409Nb	Z 13 Nb
EXHAUST® F1	≤ 0.02	≤ 0.5	≤ 0.8	≤ 0.5	17.8 - 18.8	≤ 0.5	≤ 0.5	Nb: 0.05 + 7x(C+N) - 0.5	*(430LNb)	18 L Nb
EXHAUST® F1 Evo	≤ 0.03	0.5 - 1.5	≤ 0.8	≤ 0.5	17.8 - 18.8	≤ 0.5	≤ 0.5	Nb: 0.05 + 7x(C+N) - 0.6	*(430LNbSi)	18 L Nb Si
EXHAUST® Bi Stab	≤ 0.03	≤ 1.5	≤ 1.0	≤ 0.5	17.5 - 19.5	≤ 0.5	≤ 0.5	Nb: 8xC - 0.8 / Ti: 10xC - 0.5	*(430LNbTi)	18 L Nb Ti
UGIWELD™ 439	≤ 0.03	≤ 0.8	≤ 0.8	≤ 0.5	17.0 - 18.0	≤ 0.5	≤ 0.5	Ti: 10xC - 1.1	ER439	Z 18 L Ti
UGIWELD™ 439M	≤ 0.03	0.8 - 1.0	≤ 0.8	≤ 0.5	17.0 - 19.0	≤ 0.5	≤ 0.5	Ti: 10xC - 1.1	(ER439)	Z 18 L Ti Si
UGIWELD™ 410L	≤ 0.05	≤ 0.5	≤ 0.6	≤ 0.5	12.0 - 13.5	≤ 0.5	≤ 0.5		ER410	13 L
UGIWELD™ 410NiMo	≤ 0.05	≤ 0.5	≤ 0.6	4.0 - 5.0	11.0 - 12.5	0.4 - 0.7	≤ 0.5		ER410NiMo	13 4
Duplex										
UGIWELD™ 25.9.4	≤ 0.03	≤ 1	≤ 2.5	8.0 - 10.5	24.0 - 27.0	2.5 - 4.5	≤ 1.5	N: 0.2 - 0.3 / W ≤ 1	ER2594	Z 25 9 4 N L
UGIWELD™ 312	≤ 0.15	0.30 - 0.65	1.0 - 2.5	8.0 - 10.5	28.0 - 32.0	≤ 0.75	≤ 0.75		ER312	29 9
UGIWELD™ 45N	≤ 0.03	≤ 0.9	0.5 - 2.0	7.5 - 9.5	21.5 - 23.5	2.5 - 3.5	≤ 0.5	N: 0.1 - 0.2	ER2209	22 9 3 N L
UGIWELD™ 52N	≤ 0.03	≤ 1.0	≤ 1.5	4.5 - 6.5	24.0 - 27.0	2.9 - 3.9	1.5 - 2.5	N: 0.1 - 0.25	ER2553	Z 25 5 3 Cu N L

* Usual designation not referenced in the AWS A5.9 standard

Grades	Chemical composition										Standards		
	C	Si	Mn	Ni	Cr	Mo	Cu	Fe	Other elements	AWS A5.14	ISO 18274	WNr.	
Nickel-based and cobalt-based													
UGIALLOY® 22	≤ 0.01	≤ 0.08	≤ 0.5	≥ 49.0	21.0 - 22.5	12.5 - 14.5	≤ 0.5	2.0 - 5.0	W: 2.5 - 3.5 / Co ≤ 2.5 / V ≤ 0.3	ERNiCrMo-10	Ni 6022	2.4635	
UGIALLOY® 55	≤ 0.05	≤ 0.3	≤ 1.0	54.0 - 56.0			≤ 0.5	Bal.		* ERNiFeCr		2.4472 & 2.4560	
UGIALLOY® 59	≤ 0.01	≤ 0.1	≤ 0.5	≥ 56.0	22.0 - 24.0	15.0 - 16.5	≤ 0.5	≤ 1.0	Ti ≤ 0.5 / Al: 0.1 - 0.4 / V ≤ 0.3	ERNiCrMo-13	Ni 6059	2.4607	
UGIALLOY® 61	≤ 0.05	≤ 0.7	≤ 0.7	≥ 94.0			≤ 0.25	≤ 1.0	Ti: 2.5 - 3.5 / Al ≤ 0.1	ERNi-1	Ni 2061	2.4155	
UGIALLOY® 82	≤ 0.05	≤ 0.1	2.5 - 3.5	≥ 67.0	18.0 - 22.0		≤ 0.5	≤ 3.0	(Nb+Ta): 2.0 - 3.0 / Ti ≤ 0.7	ERNiCr-3	Ni 6082	2.4806	
UGIALLOY® 182	≤ 0.02	≤ 0.5	2.5 - 3.5	≥ 61.0	15.0 - 18.0		≤ 0.3	5.0 - 6.0	(Nb+Ta): 1.5 - 2.5 / Ti ≤ 0.5	** ENiCrFe-3		2.4620	
UGIALLOY® 200	≤ 0.10	≤ 0.25	≤ 0.35	≥ 99.2			≤ 0.25					2.4066	
UGIALLOY® 276	≤ 0.02	≤ 0.08	≤ 1.0	≥ 50.0	15.0 - 16.5	15.0 - 17.0	≤ 0.5	4.0 - 7.0	W: 3.2 - 4.2 / Co ≤ 1.0 / V ≤ 0.35	ERNiCrMo-4	Ni 6276	2.4886	
UGIALLOY® 413	≤ 0.05	≤ 0.2	≤ 1.0	29.0 - 32.0			Bal.	0.4 - 0.75	Ti: 0.2 - 0.5 / Pb ≤ 0.01	*** ERCuNi		2.0837	
UGIALLOY® 418	≤ 0.10	≤ 0.5	3.0 - 4.0	64.0 - 67.0			28.0 - 32.0	≤ 0.6	Ti: 1.6 - 2.5 / Al ≤ 0.5	ERNiCu-7	Ni 4060	2.4377	
UGIALLOY® 617	≤ 0.01	≤ 0.5	≤ 0.5	≥ 44.0	21.0 - 24.0	8.5 - 9.5	≤ 0.5	≤ 1.0	Co: 11.0 - 13.0 / Al: 1.0 - 1.5 / Ti ≤ 0.6	ERNiCrCoMo-1	Ni 6617	2.4627	
UGIALLOY® 625	≤ 0.03	≤ 0.5	≤ 1.0	≥ 60.0	21.0 - 23.0	8.5 - 9.5	≤ 0.5	≤ 1.0	(Nb+Ta): 3.2 - 4.0	ERNiCrMo-3	Ni 6625	2.4831	
UGIALLOY® 686	≤ 0.01	≤ 0.1	≤ 0.1	≥ 49.0	19.0 - 23.0	15.0 - 17.0	≤ 0.5	≤ 2.0	W: 3.0 - 4.4 / Al ≤ 0.5 / Ti ≤ 0.25	ERNiCrMo-14	Ni 6686	2.4606	
UGIALLOY® 718	≤ 0.08	≤ 0.03	≤ 0.03	50.0 - 55.0	17.0 - 21.0	2.8 - 3.3	≤ 0.3	≤ 24.0	(Nb+Ta): 4.8 - 5.5 / Ti: 0.7 - 1.1 / Al: 0.2 - 0.8	ERNiFeCr-2	Ni 7718	2.4667	
UGIALLOY® 825	≤ 0.01	≤ 0.5	≤ 1.0	38.0 - 46.0	19.5 - 23.5	2.5 - 3.5	1.5 / 3.0	≥ 22.0	Ti: 0.6 - 1.2 / Al ≤ 0.2	ERNiFeCr-1	Ni 8065	2.4858	
UGIALLOY® NCW	≤ 0.01	≤ 0.5	≤ 1.0	≥ 58.0	21.5 - 22.5	9.5 - 10.5	≤ 0.3	≤ 1.0	W: 2.5 - 3.5 / Al ≤ 0.4 / Ti ≤ 0.4	ERNiCrMo-20	Ni 6660		

Grade referenced in the standard:

* AWS A5.15

** AWS A5.11

*** AWS A5.7

For any other requirements, please contact us.



Swiss Steel Group

wiresales@swisssteelgroup.com

www.swisssteel-group.com

The information and data presented here in are typical or average values and are not a guarantee of maximum or minimum values. Only the information reported on our material certificates is to be considered as relevant.

Applications specifically suggested for material described herein are made for the purpose of illustration only to enable the reader to make its own evaluation and are not intended as warranties, either express or implied, of fitness for any purposes.